

Teledyne RESON

SeaBat[®] T20-P

High resolution multibeam echosounder



Superior acoustic quality engineered for the demanding marine environment

The T20-P is a new addition to the leading SeaBat product range engineered from the ground up to evolve with your business. Combined with the Portable Sonar Processor the T20-P provides uncompromised survey data in a highly portable waterproof package designed for small vessel use.

The solution includes a range of powerful software features at an attractive price, with the option for future feature expansions to grow with your needs.

The T20-P can be supplied in ruggedized flight cases with total weight and dimensions suitable for check-in on commercial airlines and can be transported by one person.

T20-P Standard configuration

Portable Sonar Processor:

- Reduced cable connections – fast mobilization
- Single-point, accurate, sensor time-tagging
- Water-resistant IP54 rated
- 24VDC and 100-230VAC for maximum flexibility
- 10m cable to wet-end components

T20 sonar head assembly

- 190 – 420kHz wide-band
- Robust titanium housing
- Less than 8kg in water

3 years warranty

Our hardware is quality-tested to meet the most demanding standards, and backed by the full support of our comprehensive after-sales program, and 3 years of warranty you can be sure that the T20-P won't let you down.

PRODUCT BENEFITS

Product features

- Sonar User Interface - highly configurable to suit your needs.
- Snippets & sidescan backscatter
- Full water column backscatter
- Tracker – powerful tool for automated control
- Selectable Beam Density – you can define what you need to get the job done

Optional extra features

- X-Range - improve range and reduce external noise
- Multi-Detect - Multiple detections for enhanced detail over complex features and water column targets
- FlexMode – increase data density where you need it most
- Pipe Detection & Tracking – unique to SeaBat, optimize detection of pipes
- Full Rate Dual Head

SEABAT T20-P SYSTEM SPECIFICATIONS

Input voltage	24VDC or 100-230VAC 50/60Hz				
Power (typical / max)	200W / 300W				
Ingress protection	Water resistant (IP54)				
TRANSDUCER CABLE LENGTH	10m (standard), 25m, 50m, 100m (optional)				
Temperature (operational / storage)	Portable Sonar Processor: -5°C to +45°C / -30°C to +70°C Sonar wet-end: -2°C to +36°C / -30°C to +70°C				
	Height [mm]	width [mm]	depth [mm]	weight [kg/air]	weight [kg/water]
T20 Rx (EM7219)	102.0	254.0	123.0	5.0	2.2
T20 Tx (TC2181)	86.6	93.1	280	5.4	3.4
Portable Sonar Processor	131	424	379	14	N/A
T20 Acoustic performance	400kHz (max. frequency)			200kHz(min. frequency)	
Across-track receiver beam width¹	1° (center)			2° (center)	
Along-track beam width¹	1°			2°	
Number of beams	Min 10, Max 1024				
Swath coverage (up to)	140° Equi distance 165° Equi Angle (12x water depth with dual head)				
Typical Depth (CW²)	0.5-150 meters			0.5-375 meters	
Max Depth (CW³)	250 meters			550 meters	
Typical Depth (FM²)	0.5-180 meters			0.5-450 meters	
Max Depth (FM³)	300 meters			575 meters	
Ping rate (range dependent)	Up to 50 pings/s				
Pulse length (CW)	15 – 300µs				
Pulse length (FM)	300µs – 10ms				
Depth resolution	6mm				
Depth rating (sonar head)	50 meters				

For relevant tolerances for dimensions above and detailed outlined drawings see Product Description

1 Nominal values

2 This is a depth range within which the system is normally operated, from the minimum depth to a depth value corresponding to the max. swath -50%.

3 This is the single value corresponding to the depth at which the swath is reduced to 10% of its max. value. For actual swath performance refer to Product Description.

4 An extinction coverage of +/-20° is observed at about 530 meter water.

T20-P Scope of supply

- Receiver EM7219
- Projector TC2181
- Portable Sonar Processor
- 10m Receiver cable
- 10m Projector cable
- Waterproof cable set
- Wet-end bracket

Optional extras

- Normalized backscatter
- 25m, 50m, 100m cable
- Fairing
- Dual head bracket
- Motion and positioning sensors
- RESON Sound Velocity Probes
- RESON Teledyne PDS Survey Package
- RESON Service Level Agreements (SLA)